

# Technical Information

No. FO 5432

Edition: 01/06 - subject to change

Supersedes: 04/05

Status: valid



# Longlife Metal Halide Lamp

## 4ArXS HSD<sup>®</sup> 250W/60

### ■ 4ArXS – For Architainment eXtreme Seal

The OSRAM 4ArXS HSD<sup>®</sup> 250W/60 is an ultra-longlife metal halide lamp with outer bulb and daylight-like 6000 K. The lamp is characterized by a high luminance and - with 2,000 hours - a high average service life. The "eXtreme Seal" technology enables higher pinch temperatures up to max. 450°C. The lamp is suitable for cold start only. The 4ArXS HSD<sup>®</sup> 250W/60 is perfect for use in effect and architectural effect lighting.

### ■ Technical data

Lamp / order reference		4ArXS HSD <sup>®</sup> 250W/60
Rated wattage	W	250
Rated voltage	V	90
Rated lamp current (~)	A	3.1
Ignition voltage (cold)	kV <sub>s</sub>	2.0
Luminous flux	lm	17,000
Color rendering index	CRI	> 85
Color temperature	K	6,000
Arc length	mm	5.0
Lamp length (overall) l <sub>1</sub>	mm	max. 108
Bulb diameter d	mm	max. 23
LCL (a)	mm	55
Average service life	h	2,000
Base		GY 9,5

### ■ Lamp operation

Maximum permissible base temperature °C 450 at Molybdenum foil / Pinch seal region (eXtreme Seal Technology)

Cooling Convection or Fan

Burning position any

The 4ArXS HSD<sup>®</sup> 250W/60 can be operated on electronic power supplies (ECG) and standard ballasts.

### ■ Selection of igniters and control gear

Igniters: ERC 640041

Ballasts: ERC 686823

ECG: Schiederwerk EVG 2-25; Mitronic PE Line 400-700; Rotec MEB250MH/HPS-U

Further information on operating and control device requirements is available with the OSRAM brochure "Guidelines for Control Gear and Igniters - Metal Halide Lamps Display/Optic", order reference 123T01E.

### ■ Safety instruction

Because of the high UV radiation emitted by 4ArXS HSD<sup>®</sup> lamps and the fact that they operate at high pressures, they may only be used in purpose-built enclosed housings. Suitable filters must be used to ensure that the UV radiation is reduced to an acceptable level.

