



## MB 2k and MB 2k/c Unidirectional Dynamic Instrument Microphone



- Smart-priced introductory microphone for amplified and acoustic instruments
- Tailored frequency response for optimal instrument reproduction
- Unidirectional dynamic element design
- Rugged all-metal construction
- Hi-ENERGY® neodymium magnet for improved output and transient response
- Soft-touch finish reduces mechanical noise
- Silent on-off operation thanks to MagnaLock™ switch design
- Corrosion-resistant contacts from gold-plated XLRM-type connectors
- 15' cable included with MB 2k/c

### MB 2k and MB 2k/c Specifications

#### Element

Neodymium Dynamic

#### Polar Pattern

Unidirectional

#### Frequency Response

60 - 14,000 Hz

#### Open Circuit Sensitivity

-54 dB (1.9 mV) re 1V at 1 Pa

#### Impedance

600 ohms

#### Switch

MagnaLock™ on/off

#### Weight

11.9 oz (337 g)

#### Dimensions

7.23" (183.6 mm) long

1.63" (41.4 mm) head diameter

#### Output Connector

XLRM-type Balanced

**Accessories Furnished:** AT8470 Quiet-Flex™ stand clamp, 5/8"-27 to 3/8"-16 threaded adapter, protective pouch; 15' XLRM-XLRM cable in "c" version

