



MB 3k and MB 3k/c Unidirectional Dynamic Vocal Microphone



- Standout performance microphone for lead, back-up and choral vocals
- Extended frequency response for optimal vocal reproduction
- Unidirectional dynamic element design
- Rugged all-metal construction
- Hi-ENERGY® neodymium magnet for improved output and transient response
- Soft-touch finish for a secure, comfortable grip
- Silent on-off operation thanks to MagnaLock™ switch design
- Corrosion-resistant contacts from gold-plated XLRM-type connectors
- 15' cable included with MB 3k/c

MB 3k and MB 3k/c Specifications

Element

Neodymium Dynamic

Polar Pattern

Unidirectional

Frequency Response

60 - 14,000 Hz

Open Circuit Sensitivity

-54 dB (1.9 mV) re 1V at 1 Pa

Impedance

600 ohms

Switch

MagnaLock™ on/off

Weight

12.1 oz (343 g)

Dimensions

7.56" (192 mm) long

2.12" (53.8 mm) head diameter

Output Connector

XLRM-type Balanced

Accessories Furnished: AT8470 Quiet-Flex™ stand clamp, 5/8"-27 to 3/8"-16 threaded adapter, protective pouch; 15' XLRM-XLRM cable in "c" version

