

Halo Fresnel 100W

Product Code: SG HALOFWWM

Theather projector Fresnel COB 100W





Description

HALO LED MINI as well as HALO LED is the result of a Sagitter project, which can replace the most common incandescent theatre projectors with a product boasting low power consumption and the same lighting efficiency as the most common incandescent sources. The combination of a cutting

edge power supply system and a next generation 3200K white COB LED source, makes the projector suitable for stages of any size. The optics equipment features the ability to manually modify the projection angle with a high precision zoom system.

Technical Specifications

Light Source

- 1x100W Led COB Warm white 3200K
- $CRI \ge 85Ra$
- LED lifes pan: > 50.000h
- LED refresh frequency: > 400Hz flicker-free

Optic system

- Beam Angle: manual zoom from 15° to 55°
- Luminous flux: 1683lux @ 5mt (15°)
- Luminous flux: 886lux @ 5mt (55°)

Color system

• LED source COB warm white 3200K

Effects

- Linear dimmer 0-100%
- Strobe: electronic 1-20 flashes/s with adjustable speed

Control and programming

- 2 DMX configurations available: 1/2 channels
- Protocol USITT DMX 512
- Manual dimmer mode

Structure and cabinet

- Aluminium housing black color
- LCD blue graphic display
- Mounting points: single bracket
- Rotating barndoor with "safety cable" included
- XLR 3/5-poles DMX IN/OUT connection
- IP rating: IP20
- Controlled forced air fan cooling system "low noise"

Power supply

- Input Voltage: AC~100-240V, 50/60 Hz
- Switching power supply unit
- Power consumption: 150W
- IN/OUT power connection with PowerCON sockets
- Power supply cable 1mt included
- Max 4 pcs linkable @ 240V

Weight and Dimensions:

- Net weight: 7 kg
- Dimensions: 260x330x310 mm (without barndoor)

