



---

# BATI 4 DL

*Product Code: SG BATI4DL*

Led battery projector 4x12W led RGBWA-UV



## Description

Bati 4 DL is a portable battery projector, which offers a large number of cutting edge technological solutions. As LED source has been chosen one of the strongest and most effective already used in successful lines as Slimpar and Slimbar, it is a source comprising 4 LED of 12W with DL technology

(dark light) RGBWA-UV full color 6 in 1, able of satisfy even the most complex color requirements. Power is provided by a lithium, high capacity battery, that makes this projector truly portable and can be recharged many times, avoiding the "memory" effect. There are four control possibilities of Bati 4 DL: DMX with cable, IRC (remote control included), Wireless DMX, WIFI (directly from your smartphone or tablet without the need for external uncomfortable hardware).

## Technical Specifications

---

### Light source

- 4x12W led RGBWA-UV
- LED lifespan: > 50.000h
- LED refresh frequency: > 400Hz flicker-free

### Optic system

- Beam Angle: 15°

### Color system

- LED source RGBWA-UV
- Infinite chromatic possibilities

### Effects

- Linear dimmer 0-100%
- Adjustable strobe effect
- Static color mode: manual adjustment for each color
- Manual color mode: static built-in color macros
- Auto mode: built-in automatic programs with adjustable speed
- Sound mode: sound activation with internal microphone with adjustable sensitivity

### Control and programming

- 2 DMX configurations available: 6/10 channels
- Protocol USITT DMX 512
- Built-in Wi-Fi protocol for direct control by smartphone with App
- Built-in DMX wireless receiver (DMX wireless transmitter SG BATI4TX, sold separately)
- Remote controller included
- Master/Slave mode
- Auto mode

### Structure and programming

- Metal housing
- LCD color graphic display
- "Light up" positioning with adjustable angle
- IP rating: IP20
- 3-poles DMX IN/OUT
- Convection cooling system without fans

### Power supply

- Input Voltage: AC~100-240V, 50/60 Hz, for normal working and battery recharge
- Switching power supply unit
- Battery recharge with flight case: 12VDC
- Internal rechargeable battery: 12VDC
- Capacity: 8,8 Ah
- Runtime battery: ~ 8 hrs (full ON)
- Charging cycle: ~ 3 hrs (led blackout when charging)
- Power consumption: 50W

- Power IN/OUT connection with powerCON socket

**Weight and dimensions**

- Net weight: 2,5 kg (projector) – 0,3 kg (wireless transmitter)
- Dimensions: 138x138x200 mm (projector)  
147x73x40 mm (wireless transmitter)