

R-2 W, 3000K Rail-Light

Specifications	Optics	Light source	3000K
		LEDs expected lifetime	50,000 hours*
		Interchangeable lens option	25° / 35°
	Photometric	Light output	3000lm
		Optical efficacy	115 lm/W
		CRI	>80
	Features	Pan/Tilt	330° / 270°
	Electrical	AC Power nominal	100 - 240 V 50/60 Hz
		AC Power max rating	90-264V 50/60Hz
		Maximum power consumption	32W
		Typical power consumption	28W
		Power factor	0.90 PF (230 V)
	Programming and Control	Protocol	CRMX, W-DMX™ G2, W-DMX G3, W-DMX G4, W-DMX G4S
		Setting and addressing	Wireless DMX (LumenRadio)
		DMX channel	Software upgradable via wireless 1
	Physical	Dimensions (L x W)	224 x 187 mm (8,8 x 7,4 in)
		Spot diameter	Ø 104 mm (4,1 in)
		Weight	1 kg (2,2 lbs.)
		Material	Aluminium, Stainless steel, ABS
		Lens	PMMA
		IP class	IP20
	Installation	Mounting	Track mount
		Orientation	Any
	Thermal	Temperature range, Operating	-10° to +40°C (-14° to +104°F)
		Humidity (max.)	95%
		Cooling	Passive cooling
	Connections	Power	Track mount adapter
		DMX	Wireless (Lumen Radio)
	Conforms to	2006/95/EC: Low Voltage Directive	EN 60598-1, EN 60598-2-1, EN 60598-2-17, EN 62471
		1999/5/EC: R&TTE Directive	EN301489-1, EN301489-3, EN300328
		RoHS2 Directive	2011/65/EU
	Included Items	Included Items	User manual Pin key tool
	Fixtures and Accessories	Fixtures	Order no: 84010101 - R-2 W, 3000K, white, 25 deg Order no: 84010102 - R-2 W, 3000K, black, 25 deg
		Accessories	Order no: 83062011 - SGM USB uploader cable Order no: 80070229 - Lumen Radio transmitter DMX (Only) Order no: 80070230 - Lumen Radio transmitter DMX/RDM

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)