



Slimpar 7 DL

Product Code: SG SLIMPAR7DL

Projector Slimpar DL 7X12W led RGBWU/FC IRC (included)



Description

SLIMPAR rewrites lighting techniques. The line was completely designed to meet the needs of occasional users; the main feature of the projectors of this new line are asy to use, as all the functions of the projector have been fully simplified and optimised, by adding the IR control

(included) that facilitates all the operations, giving the possibility to recall "preset" programs or colours without using the DMX signal. The Slimpar line also offers different "sizes" and "sources" among the variety of colour possibilities, as well as the next generation DL (Dark Light) technology. By using these innovative 6 in 1 RGBWAU high efficiency LED sources it is possible to achieve ultraviolet light, which is now so popular in many dance events, while maintaining the many other colour shades reproduced by "full colour" RGBWA, RGBW, RGB sources. The body of all Slimpar projectors is made of ABS plastic ensuring maximum strength; the limited size offers various possibilities of use and suspended installation, thanks to the practical anchoring brackets and in the supported "light up" position, using the unique design of the projector directly.

Technical Specifications

Light source

- 7x12W led RGBWAU Full Color
- LED lifespan: >50.000h
- LED refresh frequency: >400Hz flicker free

Optic system

- Beam angle: 25°
- Luminous flux: 2290 lux @3mt (25°)

Color system

- LED source 6 in 1 RGBWAU Full Color
- Infinite chromatic possibilities and colour temperature control
- Color temperature control with Amber color
- "Dark Light" technology LED UV (Ultra Violet)
- 2 color macros can be recalled by DMX

Effects

- Linear Dimmer 0-100%
- Electronic strobe: 1-20 flashes/s with adjustable speed

Control and programming

- 4 DMX configurations available: 1/6/7/10 channels
- Protocol USITT DMX 512
- Master / Slave mode
- Sound mode with adjustable mic sensitivity
- Static color mode with independent adjustment of strobe
- Automatic mode with 2 different programs selectable from the display with independent adjustment of the speed and strobe
- Color mode with 50 different pre-programmed color macros with independent adjustment of the strobe
- IR remote controller included with possibility to recall colors or macros

Structure and cabinet

- ABS housing, black color
- Red LED display
- Mounting points: double adjustable bracket
- "light up" positioning without brackets
- 3-poles XLR in/out connection
- IP rating: IP 20
- Forced air fan cooling system

Power supply

- Input Voltage: AC~100-240V 50/60Hz
- Switching power supply unit
- Power consumption 100W
- Power IN/OUT connection with VDE socket
- Power supply cable 1,5 mt included
- Max 6 pcs linkable @240V

Weight and dimensions

- Net weight: 2,1 kg
- Dimensions: 257x130x240 mm